

Subject: Order Acknowledgement
From: websupport@newark.com
Date: Wed, 13 Aug 2008 23:48:54 +0000 (GMT)
To: pkammel@uiuc.edu

Dear Peter Kammel,

Thank you for placing the following order online with Newark.

Customer Order Reference Number : 158780174

Date Order Was Placed : 8/13/08 11:48 PM

<u>Part Num.</u>	<u>Quantity</u>	<u>Availability</u>	<u>Line Price</u>	<u>Description</u>	<u>Mfr Part #</u>	<u>Mfr Name</u>
01H0068	5		6.00	Wirewound Resistor; Series:AC; Resistance:82ohm; Resistance Tolerance:+/-5%; Power Rating:1W; Resistor Element Material:Wirewound; Voltage Rating:9VDC; Temperature Coefficient:-80 to 140 ppm; Leaded Process Compatible:Yes RoHS Compliant: Yes	AC01W82R00J	BC COMPONENTS
79K4337	5		41.55	Solid-State PC Board Relay; Contacts:SPST-NO; Control Voltage Min:3VDC; Control Voltage Max:9VDC; Output Device:Bipolar Transistor; Output Voltage Min:3VDC; Output Voltage Max:60VDC; Load Current Max:1A; Switching:DC Switch RoHS Compliant: Yes	DO061A	CRYDOM
41K6148	5		5.95	Timer IC; Package/Case:8-DIP; Current Rating:200A; Peak Reflow Compatible (260 C):Yes; Supply Current:15mA; Supply Voltage:18V; Supply Voltage Max:18V; Timer Type:Timer; Mounting Type:Through Hole RoHS Compliant: Yes	LM555CN/NOPB	NATIONAL SEMICONDUCTOR
78K6011	5		1.44	Timer IC; Package/Case:8-SOP; Current Rating:15A; Leaded Process Compatible:Yes; No. of Channels:1; Peak Reflow Compatible (260 C):Yes; Supply Voltage Max:16V; Supply Voltage Min:4.5V; Timer Type:Timer; Mounting Type:Surface Mount RoHS	LM555CM	FAIRCHILD SEMICONDUCTOR

14H0907 5	2.20	Compliant: Yes Pushbutton Switch; Illumination:Non-Illuminated; Actuator Style:Round; Actuator Diameter:6mm; Circuitry:SPST; Switch Operation:Off-(On); Switch Terminals:Through Hole; Contact Current Max:50mA; Actuator Color:Black RoHS Compliant: Yes	FSM102	TYCO ELECTRONICS
10M6416 10	0.43	Small Signal Diode; Package/Case:DO-35; Mounting Type:Through Hole; Forward Current:0.2A RoHS Compliant: Yes	1N914	NTE ELECTRONICS
70K9680 10	0.33	Aluminum Electrolytic Capacitor; Capacitor Type:General Purpose; Voltage Rating:25VDC; Capacitor Dielectric Material:Aluminum Electrolytic; Operating Temperature Range:-40 C to +85 C; Body Diameter:5mm; Body Length:11mm RoHS Compliant: Yes	MCGPR25V106M5X11-RH	Multicomp Passives
38M3144 10	0.32	Aluminum Electrolytic Capacitor; Capacitor Type:General Purpose; Voltage Rating:25VDC; Capacitor Dielectric Material:Aluminum Electrolytic; Operating Temperature Range:-40 C to +85 C; Capacitance:100uF RoHS Compliant: Yes	25YK100M5X11	
21F640 5	18.00	Pushbutton Switch; Illumination:Non-Illuminated; Actuator Style:Round; Actuator Diameter:0.157"; Circuitry:SPST; Switch Operation:(On); Switch Terminals:Through Hole; Contact Current Max:1A; Actuator Color:Black; Features:Plunger RoHS Compliant: Yes	8531MCQE2	C&K COMPONENTS
62J1377 5	11.30	Cermet Potentiometer; Series:3296; Track Resistance:1Mohm; Resistance Tolerance:+/-10%; 3296P-1-105LF Power Rating:0.5W; Operating Temperature Range:-55 C to +150 C;		BOURNS, INC.

Resistor Element
Material: Cermet;
Temperature
Coefficient: +/-100 ppm
RoHS Compliant: Yes
Carbon Film Resistor;
Series: MCCFR;
Resistance: 10kohm;
Resistance Tolerance: +/-5%;
Power Rating: 0.25W;
Operating Temperature
Range: -55 C to +155 C;
Resistor Element
Material: Carbon Film;
Voltage Rating: 250VDC
RoHS Compliant: Yes

58K5002 10

1.26

MCCFR0W4J0103A50

Multicomp Passives

Shipping : \$0.00
Direct Ship Charge : \$0.00
Tax : \$0.00
Total (excl. Tax & Shipping) : \$88.78

Shipping Method : Standard Delivery - 2-3 Day Delivery at Ground Rate (Order by 9:30 PM EST)
Payment Method : Credit Card

Delivery Address

=====
Peter Kammell
Peter Kammell
2601 Cherry Hills Dr

Champaign
IL
US
61822

Invoice Address

=====
Peter Kammell
Peter Kammell
2601 Cherry Hills Dr

Champaign
IL
US
61822

Many Thanks!
Newark